

Package ‘makemyprior’

May 18, 2021

Type Package

Title Intuitive Construction of Joint Priors for Variance Parameters

Version 1.0.0

Description Tool for easy prior construction and visualization. It helps to formulate joint prior distributions for variance parameters in latent Gaussian models. The resulting prior is robust and can be created in an intuitive way. A graphical user interface (GUI) can be used to choose the joint prior, where the user can click through the model and select priors. An extensive guide is available in the GUI. The package allows for direct inference with the specified model and prior. Using a hierarchical variance decomposition, we formulate a joint variance prior that takes the whole model structure into account. In this way, existing knowledge can intuitively be incorporated at the level it applies to. Alternatively, one can use independent variance priors for each model component in the latent Gaussian model.

License GPL (>= 2)

Date 2021-05-18

Encoding UTF-8

LazyData true

Imports ggplot2, Matrix, knitr, shiny, shinyjs, shinyBS, visNetwork, rmarkdown, rlang, MASS, testthat (>= 2.1.0)

Suggests rstan (>= 2.21.2), INLA (>= 20.03.17)

Depends R (>= 3.6.0)

Additional_repositories <https://inla.r-inla-download.org/R/stable/>

VignetteBuilder knitr

RoxygenNote 7.1.1

NeedsCompilation no

Author Ingeborg Gullikstad Hem [cre, aut],
Geir-Arne Fuglstad [aut],
Andrea Riebler [aut]

Maintainer Ingeborg Gullikstad Hem <ingeborg.hem@ntnu.no>

Repository CRAN

Date/Publication 2021-05-18 11:00:03 UTC

R topics documented:

compile_stan	2
create_stan_file	3
eval_pc_prior	4
expit	5
extract_posterior_effect	6
extract_posterior_parameter	6
find_pc_prior_param	7
inference_inla	8
inference_stan	9
latin_data	10
logit	11
makemyprior_example_model	12
makemyprior_gui	13
makemyprior_models	14
makemyprior_plotting	15
make_prior	16
mc	17
neonatal_data	19
plot.mmp_prior	20
plot_marginal_prior	21
plot_posterior_fixed	22
plot_posterior_stan	22
plot_posterior_variance	23
plot_prior	24
plot_several_posterior_stan	25
plot_tree_structure	26
print.mmp_prior	26
scale_precmat	27
summary.mmp_prior	28
typical_variance	29
wheat_data	29
Index	31

 compile_stan

Compile stan-model

Description

Function that compiles the stan-code for inference that is included in the model. The compiled version is stored in a .rds-file, which is by default stored in tempdir(). Can also be stored in the package (permanent = TRUE), or in a custom directory. In the latter case, this custom directory must be specified every time [inference_stan](#) is called. This will also be done by [inference_stan](#), but this way can save some time if it is not already pre-compiled.

Usage

```
compile_stan(save = FALSE, permanent = FALSE, path = NULL)
```

Arguments

save	Whether to save stan-file to location in package or not, defaults to FALSE. Must be in interactive session to save the object to a file.
permanent	If TRUE, the file is stored in the package directory. If FALSE (default), the file is saved in <code>tempdir()</code> .
path	Only used if file cannot be saved in the package folder. This is a path to a folder where the file is stored, do not specify a name for the file! (It will be called "full_file.rds", and should not be changed.) This argument makes the permanent argument being ignored.

Details

Note that you will get a message saying something about integer division. The PC priors on variance proportions are represented by splines, and to evaluate them in Stan we look up values, and use integer division for this. This is not a problem.

Value

Returns the stan-model invisibly.

Examples

```
## Not run:
compile_stan(save = TRUE) # saving in tempdir()

## End(Not run)
```

create_stan_file	<i>Create a "skeleton" for custom Stan code</i>
------------------	---

Description

Makes and saves files with generic code for writing custom Stan code and still use the HD prior.

Usage

```
create_stan_file(save = FALSE, location = "")
```

Arguments

save	To confirm that files can be saved (default FALSE).
location	Path to location.

Details

Must be in an interactive session to store the code. A folder called "my_stan_code" will be created in `location`. If the folder already exists in the specified location, you get an error. The folder contains:

`main_file.stan` Main file. Can put all necessary functions here, but for a cleaner code that is easier to read, we put the functions in separate files.

`jacobian.stan` Function that automatically computes the Jacobian, needed to transform from weights and total variance parameterization to log-variance parameterization.

`prior_distributions.stan` Functions for computing the prior distributions.

The provided code is written so a random intercept model with an intercept, a group effect and a residual effect can be fitted:

`example_custom_stan.R` R script showing how one can fit a random intercept model using the provided code.

The code can be expanded to fit the desired model. This requires some knowledge about Stan. No more documentation is given, as this is merely an offer to users who want to use other models than what are provided in the package already, and will be highly model specific.

Value

Nothing.

Examples

```
## Not run:
create_stan_file(TRUE, "")

## End(Not run)
```

eval_pc_prior

Evaluate PC prior for variance proportion

Description

Evaluate PC prior for a variance proportion.

Usage

```
eval_pc_prior(x, obj, param, logitscale = FALSE)
```

Arguments

x	Values to evaluate prior in.
obj	Prior object from make_prior
param	Which weight to plot, indicated using syntax shown when printing (do not need to include the <code>w[. .]</code> part to indicate that it is a variance proportion, but can be included). Print the prior object to see syntax for each weight.
logitscale	Return prior on logitscale? (default FALSE).

Value

Returns density for the given variance proportion.

Examples

```
ex_prior <- makemyprior_example_model()
eval_pc_prior(seq(0, 1, 0.01), ex_prior, "eps/eps_a_b")
# or:
eval_pc_prior(seq(0, 1, 0.01), ex_prior, "w[eps/eps_a_b]")
```

 expit

expit

Description

Calculates inverse logit, $\exp(x)/(1+\exp(x)) = 1/(1+\exp(-x))$

Usage

```
expit(x)
```

Arguments

x	Real number
---	-------------

Value

expit value

Examples

```
expit(2)
```

```
extract_posterior_effect
```

Extract the posterior of a random effect

Description

#' Extract the posterior of a random effect in the model for inference done with Stan

Usage

```
extract_posterior_effect(obj, effname)
```

Arguments

obj An object from inference_stan.
effname Name of the effect, same name as in the data.

Value

Returns a matrix with the posterior samples of the chosen effect

Examples

```
## Not run:  
  
ex_prior <- makemyprior_example_model()  
res_stan <- inference_stan(ex_prior)  
extract_posterior_effect(res_stan, "a")  
  
## End(Not run)
```

```
extract_posterior_parameter
```

Extract the posterior parameter estimate

Description

Extract the posterior parameter estimate of a random effect variance or fixed effect coefficient when inference is done with Stan

Usage

```
extract_posterior_parameter(obj, param)
```

Arguments

obj	An object from inference_stan.
param	Name of the variance parameter, which is the same as the name of the corresponding fixed or random effect in the data. Intercept is denoted 'intercept'.

Value

Returns a vector with the posterior samples of the chosen parameter, on variance scale for variances parameters and original (the common) scale for fixed effect coefficients

Examples

```
## Not run:

ex_prior <- makemyprior_example_model()
res_stan <- inference_stan(ex_prior)
extract_posterior_parameter(res_stan, "intercept")
extract_posterior_parameter(res_stan, "a")

## End(Not run)
```

find_pc_prior_param *Find suitable PC prior parameters*

Description

Returns the U value in $P(U > \sigma) = \alpha$ for a PC prior on standard deviation given an equal-tailed credible interval $P(\text{lower} < \text{func}(x) < \text{upper}) = \text{prob}$ where x is a Gaussian variable with zero mean standard deviation sigma. Note that this function uses sampling.

Usage

```
find_pc_prior_param(
  lower,
  upper,
  alpha = 0.05,
  func = exp,
  N = 10000,
  prob = 0.95
)
```

Arguments

lower	lower end of credible interval
upper	upper end of credible interval
alpha	tail probability of the PC prior (default = 0.05)

func	function to scale Gaussian variables to match desired credible interval scale, default is the exponential function
N	number of samples to use when sampling sigma and x, default is 1e4
prob	amount of mass to put in the credible interval, default is 0.95

Value

The U-value to pass to the PC prior. NB! Store result to avoid rerunning this function, as it uses sampling. The function also prints (sampled) quantiles for the U-value that is returned.

Examples

```
find_pc_prior_param(0.1, 10)
```

inference_inla	<i>Run inference</i>
----------------	----------------------

Description

This function helps you run inference with INLA using a prior object from [make_prior](#). You must have INLA installed to run this. INLA can be installed with: `install.packages("INLA", repos = c(getOption("repos"), INLA = "https://inla.r-inla-download.org/R/stable"), dep = TRUE)`. Also see r-inla.org.

Usage

```
inference_inla(prior_obj, use_likelihoood = TRUE, print_prior = TRUE, ...)
```

Arguments

prior_obj	An object from make_prior , from makemyprior_gui (both with and without the "Close and run" option), from inference_stan , or from inference_inla (for refitting model)
use_likelihoood	Whether to sample from the prior only (FALSE, can be used for e.g. debugging or to look at the priors on variance parameters when using an HD prior), or to use the likelihood and data to get the posterior (TRUE, default).
print_prior	Whether to print a text with the chosen prior or not (default TRUE)
...	Other values to be sent to INLA. Useful arguments include <code>Ntrials</code> for the binomial likelihood. We set the default value of <code>num.threads</code> to 1 (this can however be changed). See inla for details. Can be anything sent to inla except for <code>control.expert</code> and arguments that specify priors.

Details

We cannot sample from a Jeffreys' prior since it is improper. If Jeffreys' prior is used for the total variance, the prior will be changed to a Gaussian(0,1) prior on the log total variance. This means that it does not make sense to look at the variances/standard deviations/precisions, but the variance proportions will be correct.

Value

A named list with a prior object (`prior`), an inla-object (`inla`) and some data inla requires (`inla_data`).

Examples

```
## Not run:

vignette("make_prior", package = "makemyprior")

ex_prior <- makemyprior_example_model()

posterior <- inference_inla(ex_prior)
plot(posterior)

## End(Not run)
```

inference_stan	<i>Run inference</i>
----------------	----------------------

Description

This function helps you run inference with [rstan](#) using a prior object from [make_prior](#). Note that you must install Stan: `install.packages("rstan")`, see [mc-stan.org](#).

Usage

```
inference_stan(
  prior_obj,
  use_likelihood = TRUE,
  print_prior = TRUE,
  path = NULL,
  ...
)
```

Arguments

`prior_obj` An object from [make_prior](#), from [makemyprior_gui](#), from [inference_stan](#), or from [inference_inla](#) (for refitting model)

`use_likelihood` Whether to sample from the prior only (FALSE, can be used for e.g. debugging or to look at the priors on variance parameters when using an HD prior), or to use the likelihood and data to get the posterior (TRUE, default).

`print_prior` Whether to print a text with the chosen prior or not (default TRUE)

`path` Path to folder. See [compile_stan](#). Only necessary if compiled code is stored somewhere else than in the package directory or `tempdir()`

`...` Other arguments to be sent to [sampling](#). Useful arguments include:

- `iter` number of iterations for each chain (including burn-in, 2000 is the default)
- `warmup` number of iterations for the burn-in (default is `iter/2`)
- `chains` number of chains
- `init` initial value of the model parameters on internal parameterization (log-variances and covariate coefficients)
- `seed` seed value for random number generation

See [sampling](#) for more details.

Details

We cannot sample from a Jeffreys' prior since it is improper. If Jeffreys' prior is used for the total variance, the prior will be changed to a Gaussian(0,1) prior on the log total variance. This means that it does not make sense to look at the variances/standard deviations/precisions, but the variance proportions will be correct.

Value

A named list with a prior object (`prior`), a stan-object (`stan`) and some data stan requires (`stan_data`).

Examples

```

## Not run:

vignette("make_prior", package = "makemyprior")

ex_prior <- makemyprior_example_model()

posterior <- inference_stan(ex_prior, use_likelihood = TRUE, iter = 1e4, chains = 1, seed = 1)
plot(posterior)

## End(Not run)

```

latin_data

Latin square experiment data

Description

Simulated dataset for latin square experiment with 81 observations.

Usage

```
latin_data
```

Format

A list with the following variables:

y Response

lin Covariate for linear effect of treatment

row Row indexes

col Column indexes

treat_iid, treat_rw2 Treatment indexes

Examples

```
## Not run:

vignette("latin_square", package = "makemyprior")

formula <- y ~ lin + mc(row) + mc(col) + mc(iid) +
mc(rw2, model = "rw2", constr = TRUE, lin_constr = TRUE)

prior <- make_prior(
  formula, latin_data,
  prior = list(tree = "s1 = (rw2, iid);
                s2 = (row, col, s1); s3 = (s2, eps)",
                w = list(s1 = list(prior = "pc0", param = 0.25),
                        s2 = list(prior = "dirichlet"),
                        s3 = list(prior = "pc0", param = 0.25))))

posterior <- inference_stan(prior, iter = 15000, warmup = 5000,
  seed = 1, init = "0", chains = 1)

plot(prior)
plot_tree_structure(prior)
plot_posterior_fixed(posterior)
plot_posterior_stan(posterior, param = "prior", prior = TRUE)

## End(Not run)
```

logit

logit

Description

Calculates logit, $\log(x/(1-x)) = \log(x) - \log(1-x)$

Usage

```
logit(x)
```

Arguments

x Value between 0 and 1

Value

logit value

Examples

```
logit(0.5)
```

```
makemprior_example_model
```

Returning a simple example prior object

Description

Creating a simple prior object using [make_prior](#). Used in examples of other functions in the package.

Usage

```
makemprior_example_model(seed = 1)
```

Arguments

seed A seed value for reproducing the data (default seed = 1).

Details

See example for what model is made.

Value

An object of class `mmp_prior`.

Examples

```
## Not run:

ex_model <- makemyprior_example_model()

# The function corresponds to the following model call:

set.seed(1)

data <- list(
  a = rep(1:10, each = 10),
  b = rep(1:10, times = 10)
)
data$y <- rnorm(10, 0, 0.4)[data$a] + rnorm(10, 0, 0.6)[data$b] + rnorm(100, 0, 1)

formula <- y ~ mc(a) + mc(b)

prior <- make_prior(formula, data, family = "gaussian",
  prior = list(tree = "s1 = (a, b); s2 = (s1, eps)",
    w = list(s2 = list(prior = "pc0", param = 0.25)),
    V = list(s2 = list(prior = "pc", param = c(3, 0.05)))),
  intercept_prior = c(0, 1000))

## End(Not run)
```

makemyprior_gui

Graphical prior construction

Description

This functions opens a shiny app where the specified prior can be seen, and changed. Returns an invisible object,

Usage

```
makemyprior_gui(prior, guide = FALSE, no_pc = FALSE)
```

Arguments

prior	An object from make_prior .
guide	Logical, whether to open the guide directly when the app is started. Default is FALSE. The guide can be opened in the app at any time.
no_pc	Turn off computation of the PC prior on splits when using the shiny-app, to avoid slow computations. Upon closing, the PC priors will be computed. Default is FALSE.

Value

Returns an object that can be sent to [inference_stan](#) or [inference_inla](#). Can also be sent to [make-my-prior_gui](#) again.

Examples

```
## Not run:

vignette("make_prior", package = "makemyprior")

ex_prior <- makemyprior_example_model()

new_prior <- makemyprior_gui(ex_prior)

## End(Not run)
```

`makemyprior_models` *List available priors, latent models and likelihoods*

Description

Prints available priors, latent models and likelihoods to use with [make_prior](#).

Usage

```
makemyprior_models(type = c("prior", "latent", "likelihood"), select = NULL)
```

Arguments

<code>type</code>	Which of priors, latent models and likelihoods to list. Options are prior, latent and likelihood
<code>select</code>	Which in each group to show details about. NULL gives only list what exists (default), all gives detailed information about everything in that category. Can also ask for one or more specific priors/latent models/likelihoods

Value

None.

Examples

```
makemyprior_models("prior", c("pc0", "pc1"))
makemyprior_models("latent")
makemyprior_models("likelihood", "all")
```

`makemyprior_plotting` *List of available plotting functions*

Description

Directs to this help page.

Usage

```
makemyprior_plotting()
```

Details

The available plotting functions are:

- [plot_marginal_prior](#)
- [plot_posterior_fixed](#)
- [plot_posterior_precision](#)
- [plot_posterior_stan](#)
- [plot_posterior_stdev](#)
- [plot_posterior_variance](#)
- [plot_prior](#)
- [plot_several_posterior_stan](#)
- [plot_tree_structure](#)

In addition the following functions can be used to extract posterior samples of effects and parameters:

- [extract_posterior_effect](#)
- [extract_posterior_parameter](#)

[eval_pc_prior](#) can be used to evaluate a PC prior for a weight parameter.

Value

None.

 make_prior

Making a prior object

Description

Make a prior object with all necessary information about the prior and model. The object can either be sent to [makemyprior_gui](#) or used directly for inference with Stan ([inference_stan](#)) or INLA ([inference_inla](#)).

Usage

```
make_prior(
  formula,
  data,
  family = "gaussian",
  prior = list(),
  intercept_prior = c(),
  covariate_prior = list()
)
```

Arguments

formula	A formula object, using the function mc .
data	The data used in the model, as a <code>data.frame</code> or <code>list</code> . All elements must have the same length.
family	A string indicating the likelihood family. <code>gaussian</code> with identity link is the default. <code>binomial</code> with logit link and <code>poisson</code> with log link are also possible.
prior	tree The tree structure as a string. A split is specified as <code>s1 = (a,b)</code> , where <code>(s1)</code> represents a split node and can be any name except names of the input data in <code>data</code> and the reserved <code>(eps)</code> , which is used for residuals for a Gaussian likelihood. Short names are recommended. Note that these split names are just used in the initial specification, and will not be used later as they are changed by the function automatically. The child nodes for each split are included in parentheses separated by commas, and each split is separated by semicolons. Singletons are included as <code>(a)</code> . V A named list with information on the priors on each top node and singleton, i.e., all variances. The names in the list are the top node and singleton names from the tree argument. Syntax is <code>V = list(s1 = list(prior = prior_name, param = parameter_vector))</code> . w A named list with information on the priors on each split, i.e., all variance proportions. The names in the list are the split node names from the tree argument, and is specified in the same way as the variance priors in V. Prior on residuals can be defined using <code>eps</code> in this list in the case of a Gaussian likelihood.

`intercept_prior`
Parameters for Gaussian prior on intercept, specified as a vector with mean and standard deviation. Default is (0, 1000).

`covariate_prior`
Parameters for Gaussian prior on coefficients of covariates, specified as named list, each element is a vector with mean and standard deviation. Default is (0, 1000).

Details

See [makemyprior_models](#) for details on available priors and likelihoods.

Value

Prior object.

Examples

```
## Not run:
vignette("make_prior", package = "makemyprior")

## End(Not run)

p <- 10
m <- 10
n <- m*p

set.seed(1)
data <- list(a = rep(1:p, each = m),
            b = rep(1:m, times = p),
            x = runif(n))
data$y <- data$x + rnorm(p, 0, 0.5)[data$a] +
  rnorm(m, 0, 0.3)[data$b] + rnorm(n, 0, 1)

formula <- y ~ x + mc(a) + mc(b)

prior <- make_prior(formula, data, family = "gaussian",
                  intercept_prior = c(0, 1000),
                  covariate_prior = list(x = c(0, 100)))

prior
plot(prior)
```

 mc

Define latent component

Description

Function for defining a latent component for the HD prior package. All model components must be specified, and if an HD prior is used, this is specified later

Usage

```
mc(
  label,
  model = "iid",
  constr = NULL,
  lin_constr = FALSE,
  Cmatrix = NULL,
  graph = NULL,
  ...
)
```

Arguments

label	Name of the component (short names is an advantage as they are used in the app), no default (MUST be provided)
model	Type of model, default is "iid" (see list of models: makemyprior_models).
constr	Sum-to-zero constraints on component (default TRUE)
lin_constr	Linear sum-to-zero constraint, TRUE/FALSE (only for rw2 and only for Stan)
Cmatrix	Precision for this component when model = "generic0". We recommend that the matrixes are scaled to the typical variance of the corresponding covariance matrix is 1. This can be done with scale_precmat before sending matrix to mc .
graph	Path to graph file for besag effect (see details).
...	Additional arguments used for inference. For inference with rstan or inla , the following is useful (especially for the Besag model): scale.model if TRUE, the models are scaled so the geometric mean of the variance (typical variance) is 1 And some additional arguments that can be used by inla . Useful arguments include: rankdef number defining rank deficiency of the model extraconstr extra linear constraints (in addition to constr) See f for details.

Details

The graph argument is a path to a file describing neighbouring relationship on the following form:
First row: number of elements
The rest: First number is the index of this element, second is the number of neighbours, the rest is the index numbers of all neighbours for this element. If element 1 and 4 are neighbours, 1 should have 4 in its neighbour list, and 4 should have 1.

Value

For specifying details on this latent component.

Examples

```
## Not run:

vignette("make_prior", package = "makemyprior")

## End(Not run)
```

neonatal_data	<i>Neonatal mortality data</i>
---------------	--------------------------------

Description

Simulated neonatal mortality data with 323 observations.

Usage

```
neonatal_data
```

Format

A list with the following variables:

y Response

Ntrials Number of trials for each cluster

urban Covariate indicating if cluster is urban (1) or rural (0)

nu Cluster effect indexes

v County effect indexes for iid effect

u County effect indexes for Besag effect

Examples

```
## Not run:

vignette("neonatal_mortality", package = "makemyprior")

graph_path <- paste0(path.package("makemyprior"), "/neonatal.graph")

formula <- y ~ urban + mc(nu) + mc(v) +
  mc(u, model = "besag", graph = graph_path, scale.model = TRUE)

set.seed(1)
find_pc_prior_param(lower = 0.1, upper = 10, prob = 0.9, N = 2e5)

prior <- make_prior(
  formula, neonatal_data, family = "binomial",
  prior = list(tree = "s1 = (u, v); s2 = (s1, nu)",
```

```

w = list(s1 = list(prior = "pc0", param = 0.25),
        s2 = list(prior = "pc1", param = 0.75)),
V = list(s2 = list(prior = "pc",
                  param = c(3.35, 0.05))))

posterior <- inference_stan(prior, iter = 15000, warmup = 5000,
                           seed = 1, init = "0", chains = 1)

plot(prior)
plot_tree_structure(prior)
plot_posterior_fixed(posterior)
plot_posterior_stan(posterior, param = "prior", prior = TRUE)

## End(Not run)

```

plot.mmp_prior

Plotting

Description

Plotting

Usage

```

## S3 method for class 'mmp_prior'
plot(x, ...)

## S3 method for class 'mmp_inla'
plot(x, ...)

## S3 method for class 'mmp_stan'
plot(x, ...)

```

Arguments

x	Object of class <code>mmp_prior</code> , <code>mmp_inla</code> or <code>mmp_stan</code> .
...	Additional arguments to plotting functions. Varies with what object is sent to function.

Details

See [plot_prior](#) (objects of class `mmp_prior`), [plot_posterior_stan](#) (objects of class `mmp_stan`), and [plot_posterior_variance](#) (objects of class `mmp_inla`),

Value

None.

Examples

```
## Not run:
pri <- makemyprior_example_model()
plot(pri)
res_stan <- inference_stan(pri)
plot(res_stan)
res_inla <- inference_inla(pri)
plot(res_inla)

## End(Not run)
```

plot_marginal_prior	<i>Plotting prior for a single parameter (weight or variance (not standard deviation))</i>
---------------------	--

Description

Following the parameterization of the prior.

Usage

```
plot_marginal_prior(x, obj, param, sd = FALSE)
```

Arguments

x	Values to evaluate prior in.
obj	An object from <code>make_prior</code> , <code>inference_stan</code> , <code>inference_inla</code> , or <code>makemyprior_gui</code>
param	Name of parameter to plot (see <code>print(obj)</code> for syntax). Note that only variances will be plotted, so <code>V[. .]</code> and <code>sigma^2[. .]</code> must be used to indicate those parameters.
sd	Whether to plot variance parameters on the standard deviation (TRUE) or variance (FALSE, default) scale

Value

A `ggplot` with the posterior distribution. See also [makemyprior_plotting](#).

Examples

```
ex_prior <- makemyprior_example_model()
plot_marginal_prior(seq(0, 1, 0.001), ex_prior, "w[a/a_b]")
plot_marginal_prior(seq(0, 1, 0.001), ex_prior, "w[eps/eps_a_b]")
plot_marginal_prior(seq(0, 5, 0.01), ex_prior, "V[eps_a_b]")
```

plot_posterior_fixed *Plotting posterior distributions*

Description

Function for plotting the posterior distributions of the coefficients of the fixed effects

Usage

```
plot_posterior_fixed(obj)
```

Arguments

obj An object from inference_stan or inference_inla

Value

A [ggplot](#) with the posterior distributions. See also [makemyprior_plotting](#).

Examples

```
## Not run:

ex_prior <- makemyprior_example_model()
res_stan <- inference_stan(ex_prior)
plot_posterior_fixed(res_stan)

## End(Not run)
```

plot_posterior_stan *Plotting posterior distributions*

Description

Function for plotting the posterior distributions of the random effect variances on the scale of the tree parameterization.

Usage

```
plot_posterior_stan(
  obj,
  param = c("prior", "variance", "stdev", "precision"),
  prior = FALSE
)
```

Arguments

obj	An object from inference_stan
param	A string indicating parameterization of plot. "prior" for scale of parameters, "variance", "stdev" and "precision" also possible.
prior	Include prior in the plot? Only possible for param = "prior". Note that if Jeffreys' prior is used for the total variance, it will not be included in the plot.

Value

A [ggplot](#) with the posterior distributions. See also [makemyprior_plotting](#).

Examples

```
## Not run:  
  
ex_prior <- makemyprior_example_model()  
res_stan <- inference_stan(ex_prior)  
plot_posterior_stan(res_stan)  
  
## End(Not run)
```

plot_posterior_variance

Plotting posterior variances, standard deviations or precisions

Description

Plotting posterior variances, standard deviations or precisions

Usage

```
plot_posterior_variance(obj)
```

```
plot_posterior_stdev(obj)
```

```
plot_posterior_precision(obj)
```

Arguments

obj	An object from inference_stan or inference_inla.
-----	--

Value

A [ggplot](#) object with the plot See also [makemyprior_plotting](#).

Examples

```
## Not run:  
  
ex_prior <- makemyprior_example_model()  
res_stan <- inference_stan(ex_prior)  
res_inla <- inference_inla(ex_prior)  
plot_posterior_variance(res_stan)  
plot_posterior_variance(res_inla)  
  
## End(Not run)
```

plot_prior

Plotting prior distributions

Description

Function for plotting the prior distributions of the random effects on the scale of the parameters chosen

Usage

```
plot_prior(obj)
```

Arguments

obj An object from `make_prior`, `inference_stan`, `inference_inla`, or `makemyprior_gui`

Value

A `ggplot` with the prior distributions. See also [makemyprior_plotting](#).

Examples

```
ex_prior <- makemyprior_example_model()  
plot_prior(ex_prior)
```

plot_several_posterior_stan
Plotting several posterior distributions

Description

Function for plotting the posterior distributions of the random effect variances on the scale of the tree parameterization.

Usage

```
plot_several_posterior_stan(  
  objs,  
  param = c("prior", "variance", "stdev", "precision", "logvariance")  
)
```

Arguments

objs	A names list with objects of class <code>mmp_stan</code> from <code>inference_stan</code> , can be any length (but typically length two for one prior (<code>use_likelihoood = FALSE</code>) and posterior, or two posteriors).
param	A string indicating parameterization of plot. "prior" for scale of parameters, "variance", "stdev", "precision" and "logvariance" are also possible.

Details

We cannot sample from a Jeffreys' prior since it is improper. If Jeffreys' prior is used for the total variance, the prior will be changed to a $\text{Gaussian}(0,1)$ prior on the log total variance. This means that it does not make sense to look at the variances/standard deviations/precisions, but the variance proportions will be correct. See also [makemyprior_plotting](#).

Value

A [ggplot](#) with the posterior distributions.

Examples

```
## Not run:  
  
ex_prior <- makemyprior_example_model()  
res_stan <- inference_stan(ex_prior)  
extract_posterior_variance(res_stan, "a")  
  
## End(Not run)
```

plot_tree_structure *Plotting the prior tree structure graph*

Description

Can only be used for visualization in R.

Usage

```
plot_tree_structure(obj, nodenames)
```

Arguments

obj	An object from <code>make_prior</code> , <code>inference_stan</code> , <code>inference_inla</code> , or <code>makemyprior_gui</code>
nodenames	Custom names for each node (optional). Given as a named list with the default names as list names, and the new names as list elements. Do not need to provide all.

Value

A [visNetwork](#) with the tree graph See also [makemyprior_plotting](#).

Examples

```
ex_prior <- makemyprior_example_model()
plot_tree_structure(ex_prior)
```

print.mmp_prior *Print*

Description

Print

Usage

```
## S3 method for class 'mmp_prior'
print(x, ...)

## S3 method for class 'mmp_inla'
print(x, ...)

## S3 method for class 'mmp_stan'
print(x, ...)
```

Arguments

x Object of class `mmp_prior`, `mmp_inla` or `mmp_stan`.
... For `mmp_stan` and `mmp_inla`, see [print.data.frame](#).

Value

Returns input object invisible.

Examples

```
## Not run:  
pri <- makemyprior_example_model()  
pri # or print(pri)  
res_stan <- inference_stan(pri)  
res_stan # or print(res_stan)  
res_inla <- inference_inla(pri)  
res_inla # or print(res_inla)  
  
## End(Not run)
```

scale_precmat

Scaling precision matrix

Description

Scaling a precision matrix so the corresponding covariance matrix has typical variance (geometric mean) equal to 1.

Usage

```
scale_precmat(Q)
```

Arguments

Q Precision matrix

Value

Precision matrix which is now scaled to have typical variance 1.

Examples

```
scale_precmat(diag(10))
```

summary.mmp_prior	<i>Short summary</i>
-------------------	----------------------

Description

Short summary

Usage

```
## S3 method for class 'mmp_prior'  
summary(object, ...)
```

```
## S3 method for class 'mmp_inla'  
summary(object, ...)
```

```
## S3 method for class 'mmp_stan'  
summary(object, ...)
```

Arguments

object	Object of class mmp_prior, mmp_inla or mmp_stan.
...	For mmp_stan and mmp_inla, see print.data.frame .

Value

Returns summary invisible.

Examples

```
## Not run:  
pri <- makemyprior_example_model()  
summary(pri)  
res_stan <- inference_stan(pri)  
summary(res_stan)  
res_inla <- inference_inla(pri)  
summary(res_inla)  
  
## End(Not run)
```

typical_variance	<i>Compute the typical variance</i>
------------------	-------------------------------------

Description

Computing the typical variance (geometric mean) of a matrix.

Usage

```
typical_variance(mat)
```

Arguments

mat Matrix.

Value

Typical variance.

Examples

```
typical_variance(diag(10))
```

wheat_data	<i>Genomic wheat breeding model data</i>
------------	--

Description

Simulated wheat yield data with 100 observations.

Usage

```
wheat_data
```

Format

A list with the following variables

y Response

a, b, x Indexes for the additive, dominance and epistasis genetic effects, respectively

Q_a, Q_d, Q_x Precision matrices for the genetic effects

Examples

```
## Not run:

vignette("wheat_breeding", package = "makemyprior")

wheat_data_scaled <- wheat_data
wheat_data_scaled$Q_a <- scale_precmat(wheat_data$Q_a)
wheat_data_scaled$Q_d <- scale_precmat(wheat_data$Q_d)
wheat_data_scaled$Q_x <- scale_precmat(wheat_data$Q_x)

formula <- y ~
  mc(a, model = "generic0", Cmatrix = Q_a, constr = TRUE) +
  mc(d, model = "generic0", Cmatrix = Q_d, constr = TRUE) +
  mc(x, model = "generic0", Cmatrix = Q_x, constr = TRUE)

prior <- make_prior(formula, wheat_data_scaled, prior = list(
  tree = "s1 = (d, x); s2 = (a, s1); s3 = (s2, eps)",
  w = list(s1 = list(prior = "pcM", param = c(0.67, 0.8)),
    s2 = list(prior = "pcM", param = c(0.85, 0.8)),
    s3 = list(prior = "pc0", param = 0.25)))

posterior <- inference_stan(prior, iter = 15000, warmup = 5000,
  chains = 1, seed = 1)

plot(prior)
plot_tree_structure(prior)
plot_posterior_fixed(posterior)
plot_posterior_stan(posterior, param = "prior", prior = TRUE)

## End(Not run)
```

Index

- * **INLA**
 - inference_inla, 8
- * **datasets**
 - latin_data, 10
 - neonatal_data, 19
 - wheat_data, 29
- * **formula**
 - mc, 17
- * **gui**
 - makemyprior_gui, 13
- * **plot**
 - plot_marginal_prior, 21
 - plot_posterior_fixed, 22
 - plot_posterior_stan, 22
 - plot_posterior_variance, 23
 - plot_prior, 24
 - plot_several_posterior_stan, 25
 - plot_tree_structure, 26
- * **posterior**
 - extract_posterior_effect, 6
 - extract_posterior_parameter, 6
- * **prior**
 - make_prior, 16
- * **rstan**
 - inference_stan, 9
- compile_stan, 2, 10
- create_stan_file, 3
- eval_pc_prior, 4, 15
- expit, 5
- extract_posterior_effect, 6, 15
- extract_posterior_parameter, 6, 15
- f, 18
- find_pc_prior_param, 7
- ggplot, 21–25
- inference_inla, 8, 8, 9, 14, 16
- inference_stan, 2, 8, 9, 9, 14, 16
- inla, 8, 18
- latin_data, 10
- logit, 11
- make_prior, 5, 8, 9, 12–14, 16
- makemyprior_example_model, 12
- makemyprior_gui, 8, 9, 13, 14, 16
- makemyprior_models, 14, 17, 18
- makemyprior_plotting, 15, 21–26
- mc, 16, 17, 18
- neonatal_data, 19
- plot.mmp_inla(plot.mmp_prior), 20
- plot.mmp_prior, 20
- plot.mmp_stan(plot.mmp_prior), 20
- plot_marginal_prior, 15, 21
- plot_posterior_fixed, 15, 22
- plot_posterior_precision, 15
- plot_posterior_precision
(plot_posterior_variance), 23
- plot_posterior_stan, 15, 20, 22
- plot_posterior_stddev, 15
- plot_posterior_stddev
(plot_posterior_variance), 23
- plot_posterior_variance, 15, 20, 23
- plot_prior, 15, 20, 24
- plot_several_posterior_stan, 15, 25
- plot_tree_structure, 15, 26
- print.data.frame, 27, 28
- print.mmp_inla(print.mmp_prior), 26
- print.mmp_prior, 26
- print.mmp_stan(print.mmp_prior), 26
- rstan, 9, 18
- sampling, 10
- scale_precmat, 18, 27
- summary.mmp_inla(summary.mmp_prior), 28
- summary.mmp_prior, 28

`summary.mmp_stan(summary.mmp_prior)`, [28](#)

`typical_variance`, [29](#)

`visNetwork`, [26](#)

`wheat_data`, [29](#)