

Package ‘sdm’

April 29, 2020

Type Package

Title Species Distribution Modelling

Version 1.0-89

Date 2020-04-22

Author Babak Naimi, Miguel B. Araujo

Maintainer Babak Naimi <naimi.b@gmail.com>

Depends methods, sp (>= 1.2-0), R (>= 3.0.0)

Imports raster

Suggests R.rsp, shinyBS, shiny, dismo, rmarkdown

Description An extensible framework for developing species distribution models using individual and community-based approaches, generate ensembles of models, evaluate the models, and predict species potential distributions in space and time. For more information, please check the following paper: Naimi, B., Araujo, M.B. (2016) <doi:10.1111/ecog.01881>.

License GPL (>= 3)

URL <http://biogeoinformatics.org>

VignetteBuilder R.rsp

NeedsCompilation no

Repository CRAN

Date/Publication 2020-04-29 19:00:02 UTC

R topics documented:

add	2
Arith-methods	4
as.data.frame	5
boxplot	6
calibration	7
coordinates	8
density	9

ensemble	10
evaluates	13
Extract by index	15
featuresFrame-class	16
get models' outputs	16
getVarImp	18
gui	19
installAll	21
names	22
niche	23
predict	25
rcurve	27
read.sdm	29
roc	30
sdm	32
sdmCorrelativeMethod-class	34
sdmData	35
sdmdata-class	39
sdmModels-classes	40
sdmSetting	41
subset	43
Index	45

add	<i>add a new method to the package</i>
-----	--

Description

This function is an interface to extend the package. A user can define a new method and add it to the package. When the method is successfully added, it can be used together with all existing methods. The names of available methods in the package can be seen using `getMethodNames`. It is not limited only to modelling (fitting) methods, but can be a replication method, or one to generate pseudo-absences, etc.

You can get an object of an existing method through `getMethod`.

Usage

```
add(x,w,echo,...)
```

```
getMethod(x,w,...)
```

```
getMethodNames(w,...)
```

Arguments

x	Either a list, or an object generated by <code>getmethod</code> function
w	specify which group of methods the new method belongs to. "sdm" (default) can be used for modelling method
echo	logical (default=TRUE), determines whether a message should be printed to report if the adding is successful
...	additional arguments. see details

Details

These functions provide flexibility to extend the package by adding new methods. It is also possible to add several instances of an existing method to have, for example, a method with different settings at the same time. Whetevet the new method is, it can also be shared and used by other users.

Value

`getmethod` gives an object of an appropriate class depending on w.

`getmethodNames` generate a list (if `alt=TRUE` is provided as additional argument) containing the name of methods and all alternative names (aliases) specified for each method, or a character vector (if `alt=FALSE`) containing the main names.

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, 39:368-375, DOI: 10.1111/ecog.01881

Examples

```
## Not run:  
getmethodNames('sdm')  
  
## End(Not run)
```

Description

If two sets of models fitted in two separate `sdmModels` objects, they can be merged into a single `sdmModels` objects using '+'

Value

an object of class `sdmModels`

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, 39:368-375, DOI: 10.1111/ecog.01881

Examples

```
## Not run:
file <- system.file("external/pa_df.csv", package="sdm")

df <- read.csv(file)

head(df)

d <- sdmData(sp~b15+NDVI,train=df)

d
#----

m1 <- sdm(sp~b15+NDVI,data=d,methods=c('glm','gbm'))

m1

m2 <- sdm(sp~b15+NDVI,data=d,methods=c('svm'))

m2

m <- m1 + m2

m
```

```
## End(Not run)
```

as.data.frame *Get a data.frame with record id values (rID)*

Description

Converts a sdmdata object to a data.frame. By additional arguments, it is possible to make a query on the dataset (see details).

Usage

```
## S4 method for signature 'sdmdata'  
as.data.frame(x, ...)
```

Arguments

x	sdmdata object
...	Additional arguments (optional, see details)

Details

Following additional arguments optionally can be used to get a subset of data by specifying the record IDs; or using a query by specifying the name of species, and/or the name of data groups, and/or range of times (if time information are available):

ind: an integer vector containing the record IDs; sp: a character vector of the name of species grp: a character vector of the group names (e.g., 'test'; if independent test is available) time: a vector of times (an appropriate time class or a character that can be converted into a time format)

Value

data.frame

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, 39:368-375, DOI: 10.1111/ecog.01881

Examples

```
## Not run:
file <- system.file("external/data.sdd", package="sdm")

d <- read.sdm(file)

d # a sdmdata object

df <- as.data.frame(d)
head(df)

# only the records with rID == c(1,2,3):
as.data.frame(d, ind=1:3)

## End(Not run)
```

boxplot

boxplot

Description

Make a box plot of model evaluation data, i.e., the model predictions for known presence and absence points.

Details

Arguments:

x Object of class `sdmEvaluate` names Optional, the x-axis label for the group of data (e.g., 'Absence', 'Presence') . . . Additional arguments that can be passed to [boxplot](#)

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, DOI: 10.1111/ecog.01881

Examples

```
e <- evaluates(x=c(1,1,0,1,0,0,0,1,1,1,0),
              p=c(0.69,0.04,0.05,0.95,0.04,0.65,0.09,0.61,0.75,0.84,0.15))

boxplot(e)
```

calibration

Calibration

Description

evaluates for calibration

Usage

```
calibration(x,p,nbin,weight,...)
```

Arguments

x	a numeric vector including the observed values; or a <code>sdmEvaluate</code> object
p	a numeric vector including the predicted values
nbin	number of bins to discretize the predicted values into the specified bins (default: 10); instead, it can be the keyword of 'seek' to ask for seeking the best number
weight	logical, specifies whether a weight should be calculated based on the number of records at each bin. The weight will be used to summarize the calibration statistic
...	additional arguments (not implemented yet.)

Details

The output of this function can be used in the `plot` function to generate Calibration plot. The calibration statistic is calculated using a method developed by the authors of this package (the journal article is not published yet, but in preparation)

Value

an object of class `.sdmCalibration`

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Niamir, A., Jimenez-Valverde, A., Araujo, M.B. (In preparation) Measuring calibration capacity of statistical models: a new statistic.

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, DOI: 10.1111/ecog.01881

Examples

```
ca <- calibration(x=c(1,1,0,1,0,0,0,1,1,1,0),
                 p=c(0.69,0.04,0.05,0.95,0.04,0.65,0.09,0.61,0.75,0.84,0.15))

ca

plot(ca)
```

coordinates

get or set spatial coordinates of species data

Description

Get or set spatial coordinates of a sdmdata object.

Usage

```
## S4 method for signature 'sdmdata'
coordinates(obj,...)

## S4 replacement method for signature 'sdmdata'
coordinates(object)<-value
```

Arguments

obj	speciesData (either of singleSpecies, multiple Species or SpeciesDataList) object
object	same as obj
value	spatial coordinates either a matrix, or data.frame, or column name as character, or a formula (e.g., ~x+y, or ~coords(x+y))
...	Additional arguments

Value

matrix, or if the coordinates set, the `sdmdata` object is returned.

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, DOI: 10.1111/ecog.01881

Examples

```
file <- system.file("external/data.sdd", package="sdm")
d <- read.sdm(file)

d # a sdmdata object

coordinates(d)
```

density

density

Description

Create a density plots of presence and absence data

Value

A density plot. Presence data are in darkblue, and absence data are in red.

Methods

```
density(x, ...)
```

x Object of class 'sdmEvaluate' (or a numeric vector of observed presence/absence)

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, DOI: 10.1111/ecog.01881

Examples

```
e <- evaluates(x=c(1,1,0,1,0,0,0,1,1,1,0),
              p=c(0.69,0.04,0.05,0.95,0.04,0.65,0.09,0.61,0.75,0.84,0.15))

density(e)
```

ensemble

Ensemble Forecasting of SDMs

Description

Make a Raster object with a weighted averaging over all predictions from several fitted model in a sdmModel object.

Usage

```
## S4 method for signature 'sdmModels'
ensemble(x, newdata, filename="", setting,...)
```

Arguments

x	a sdmModels object
newdata	Raster* object or data.frame, can be either predictors or the results of the predict function
filename	character, output file name
setting	list, contains the parameters that are used in the ensemble procedure; see details
...	additional arguments passed to the predict function

Details

ensemble function uses the fitted models in an sdmModels object to generate an ensemble/consensus of predictions by individual models. Several methods do exist for this procedure, that are (or will be) implemented in this function, and can be defined in the method argument. A list can be introduced in the setting argument in which several parameters can be set including:

- method: specify which ensemble method should be used. Several methods are implemented including:

- 'unweighted': unweighted averaging/mean.
- 'weighted': weighted averaging.
- 'median': median.
- 'pa': mean of predicted presence-absence values (predicted probability of occurrences are first converted to presence-absence using a threshold, then they are averaged).
- 'mean-weighted': A two step mean that is when several replications are fitted for each modelling methods (e.g., through bootstrapping or cross-validation), using this method an unweighted mean is taken over the predicted values of different replications of each method (i.e., within model averaging), then a weighted mean is used to combine them into final ensemble values (i.e., between models averaging).
- 'mean-unweighted': Same as the previous one, but an unweighted mean is also used for the second step (instead of weighted mean).
- 'median-weighted': Same as the 'mean-weighted', but the median is used instead of unweighted mean.
- 'median-unweighted': another two-step method, median is used for the first step and unweighted mean is used for the second step.
- 'uncertainty' or 'entropy': this method generates the uncertainty among the models' predictions that can be interpreted as model-based uncertainty or inconsistency among different models. It ranges between 0 and 1, 0 means all the models predicted the same value (either presence or absence), and 1 refers to maximum uncertainty, e.g., half of the models predicted presence (or absence) and the other half predicted the opposite value.
- stat: if the method='weighted' is used, this specify which evaluation statistics can be used as weight in the weighted averaging procedure. Alternatively, one may directly introduce weights (see the next argument)
- weights: an optional numeric vector (with a length equal to the models that are successfully fitted) to specify the weights for weighted averaging procedure (if the method='weighted' is specified)
- id: specify the model IDs that should be considered in the ensemble procedure. If missing, all the models that are successfully fitted are considered.
- wtest: specify which test dataset ("training", "test.dep", "test.indep") should be used to extract the statistic (stat) values as weights (if a relevant method is specified)
- opt: If either of the threshold_based stats are selected, opt can be also specified to select one of the criteria for optimising the threshold. The possible value can be between 1 to 10 for "sp=se", "max(se+sp)", "min(cost)", "criteria, respectively.
- power: default: 1, a numeric value to which the weights are raised. Greater value than 1 affects weighting scheme (for the methods e.g., "weighted") to increase the weights for the models with greater weight. For example, if weights are c(0.2,0.2,0.2,0.4), raising them to power 2 would be resulted to new weights as c(0.1428571,0.1428571, 0.1428571, 0.5714286) that causes greater influence of the models with greater performances to the ensemble output.

Value

- a Raster object if predictors is a Raster object
- a numeric vector if predictors is a data.frame object

Author(s)

Babak Naimi <naimi.b@gmail.com>
<http://biogeoinformatics.org>

References

#

See Also

#

Examples

```
## Not run:

file <- system.file("external/species.shp", package="sdm") # get the location of the species data
species <- shapefile(file) # read the shapefile

path <- system.file("external", package="sdm") # path to the folder contains the data

lst <- list.files(path=path,pattern='asc$',full.names = T) # list the name of the raster files

# stack is a function in the raster package, to read/create a multi-layers raster dataset
preds <- stack(lst) # making a raster object

d <- sdmData(formula=Occurrence~., train=species, predictors=preds)

d

# fit the models (5 methods, and 10 replications using bootstrapping procedure):
m <- sdm(Occurrence~.,data=d,methods=c('rf','tree','fda','mars','svm'),
        replicatin='boot',n=10)

# ensemble using weighted averaging based on AUC statistic:
p1 <- ensemble(m, newdata=preds, filename='ens.img',setting=list(method='weighted',stat='AUC'))
plot(p1)

# ensemble using weighted averaging based on TSS statistic
# and optimum threshold critesion 2 (i.e., Max(spe+sen)) :
p2 <- ensemble(m, newdata=preds, filename='ens2.img',setting=list(method='weighted',
        stat='TSS',opt=2))

plot(p2)

## End(Not run)
```

evaluates	<i>evaluate for accuracy</i>
-----------	------------------------------

Description

evaluates for accuracy

Usage

```
evaluates(x,p,...)
```

```
getEvaluation(x,w,wtest,stat,opt,...)
```

Arguments

x	a numeric vector including the observed values; or a <code>sdmModels</code> object
p	a numeric vector including the predicted values
w	a numeric vector indicates model IDs
wtest	which test, training, <code>dep.test</code> , or <code>indep.test</code> ?
stat	statistics that should be extracted from the <code>sdmEvaluate</code> object
opt	a numeric value indicates which threshold optimisation criteria should be considered if a threshold-based statistic is selected in <code>stat</code>
...	additional arguments (see details)

Details

Evaluates the performance (accuracy) given the observed values, and the predicted values. As additional argument, the distribution of data can be specified (through `distribution`), that can be either of `'binomial'`, `'gaussian'`, `'laplace'`, or `'poisson'`. If not specified, it will be guessed by the function!

`getEvaluation` can be used to get the evaluation results from a fitted model (`sdmModels` object that is output of the `sdm` function). Each model in `sdmModels` has a `modelID`, that can be specified in `w` argument. If `w` is not specified or more than a `modelID` is specified, then a `data.frame` is generated that contains the statistics specified in `stat`. For a single model (if `length(w)` is 1), `stat` can be 1 (`threshold_independent` statistics), or 2 (`threshold_based` statistics) or `NULL` (both groups). If more than a model is specified (`w` is either `NULL` or has a length greater than 1), `stat` can be the name of statistics such as `'AUC'`, `'COR'`, `'Deviance'`, `'obs.prevalence'`, `'threshold'`, `'sensitivity'`, `'specificity'`, `'TSS'`, `'Kappa'`. If either of the `threshold_based` stats are selected, `opt` can be also specified to select one of the criteria for optimising the threshold. The possible value can be between 1 to 10 for `"sp=se"`, `"max(se+sp)"`, `"min(cost)"`, `"minF"` criteria, respectively.

Value

an object of class `sdmEvaluate` from `evaluates` function

a list or `data.frame` from `getEvaluation` function

Author(s)

Babak Naimi <naimi.b@gmail.com>
<http://r-gis.net>
<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, DOI: 10.1111/ecog.01881

See Also

#

Examples

```
## Not run:
file <- system.file("external/model.sdm", package="sdm")

m <- read.sdm(file) # a sdmModels Object (fitted using sdm function)

getModelInfo(m)

# there are 4 models in the sdmModels objects

# so let's take a look at all the results for the model with modelID 1

# evaluation using training data (both threshod_independent and threshold_based groups):
getEvaluation(m,w=1,wtest='training')

getEvaluation(m,w=1,wtest='training',stat=1) # stat=1 (threshold_independent)

getEvaluation(m,w=1,wtest='test.dep',stat=2) # stat=2 (threshold_based)

getEvaluation(m,w=1:3,wtest='test.dep',stat=c('AUC','TSS'),opt=2)

getEvaluation(m,opt=1) # all models

getEvaluation(m,stat=c('TSS','Kappa','AUC'),opt=1) # all models

#####

example for evaluation:

evaluates(x=c(1,1,0,1,0,0,0,1,1,1,0),
          p=c(0.69,0.04,0.05,0.95,0.04,0.65,0.09,0.61,0.75,0.84,0.15))

## End(Not run)
```

Extract by index *Indexing to extract records of a sdmdata object*

Description

This function extracts records of a sdmdata object and generates a new object of the same type (if drop=FALSE; otherwise a data.frame). In sdmdata, rID is the unique ID for each record.

Methods

x[i]

Arguments

x a Raster* object
i an index: record id (rID) in sdmdata object
drop If TRUE, a data.frame is returned, otherwise a sdmdata object is returned.

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, 39:368-375, DOI: 10.1111/ecog.01881

Examples

```
file <- system.file("external/data.sdd", package="sdm")  
  
d <- read.sdm(file)  
  
# see the number of records:  
d  
  
d2 <- d[1:10]  
  
d2  
  
d3 <- d[1:10,drop=TRUE]  
  
d3
```

featuresFrame-class *featureFrame class*

Description

An S4 class contains the information of features used to fit a model

Slots

vars A character vector containing the name of variables from the dataset used to generate the features

feature.types A list containing the definition of features

response.specific NULL, or a list containing the definition of features that their definitions are according to the response variable (i.e. species)

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, DOI: 10.1111/ecog.01881

get models' outputs *Get information/modelIDs relevant to fitted models in a sdmModels object*

Description

When SDMs are fitted using the `sdm` function, a `sdmModels` object is generated containing all the information and objects created through fitting and evaluation procedures for all species and methods. To each model, a unique `modelID` is assigned. `getModelInfo` returns a `data.frame` summarising some information relevant to the fitted models including `modelID`, method name, whether the model is fitted successfully, whether and what replication procedure is used for data partitioning, etc. `getModelInfo` helps to get the unique model IDs for all or certain models given the parameters that users specify.

Usage

```
getModelId(x, success, species, method, replication, run)

getModelInfo(x, ...)
```

Arguments

x	a sdmModel object
success	logical; specifies whether the info/ids should be returned only for the models that are successfully fitted or not (default is TRUE)
species	optional; a character vector specifies the name of species for which the info should be returned (default is NULL meaning for all species)
method	optional; a character vector specifies the name of methods for which the info should be returned (default is NULL meaning for all methods)
replication	optional; a character vector specifies the name of replication method for which the info should be returned (default is NULL meaning for all species)
run	optional; a numeric vector specifies for which replication runs the info should be returned (default is NULL meaning for all runs)
...	additional arguments. see details

Details

in `getModelInfo`, as additional arguments, you can use the arguments in the function `getModelId` to specify which records should be returned.

Value

`getModelInfo`: data.frame `getModelId`: a numeric vector

Author(s)

Babak Naimi <naimi.b@gmail.com>
<http://r-gis.net>
<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, 39:368-375, DOI: 10.1111/ecog.01881

See Also

#

Examples

```
file <- system.file("external/model.sdm", package="sdm")  
  
m <- read.sdm(file)  
  
getModelInfo(m)  
  
# getModelId(m)  
  
# getModelId(m,method='glm')
```

getVarImp	<i>variable importance</i>
-----------	----------------------------

Description

Calculates relative importance of different variables in the models using several approaches.

Usage

```
getVarImp(x, id, wtest, ...)
```

Arguments

x	sdmModels object
id	numeric, specify the model (modelID) for which the variable importance values are extracted
wtest	specifies which dataset ('training', 'test.dep', 'test.indep') should be used (if exist) to calculate the importance of variables
...	additional arguments as for getModelId function

Details

getVarImp function returns an object including different measures of variable importance, and if be put in plot function, a barplot is generated. If the ggplot2 package is installed on your machine, the plot is generated using ggplot (unless you turn gg = FALSE), otherwise, the standard barplot is used.

Author(s)

Babak Naimi <naimi.b@gmail.com>
<http://r-gis.net>
<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, DOI: 10.1111/ecog.01881

Examples

```
## Not run:
# if m is a sdmModels object (output of the sdm function) then:

getVarImp(m,id=1,wtest='training') # variable importance based on training dataset

vi <- getVarImp(m,id=1,wtest='test.dep')

vi

plot(vi,'auc')

plot(vi,'cor')
#####
# You can get Mean variable importance (and confidence interval) for multiple models:

vi <- getVarImp(m,id=1:10,wtest='test.dep') # specify the modelIDs of the models

vi

plot(vi,'cor')

# you can use the getModelId function to find the id of the specific method, replication, etc.
# or you may put the arguments of the getModelId in the getVarImp function:

vi <- getVarImp(m, method='glm') # Mean variable importance for the method glm

vi

plot(vi)

plot(vi, gg = F) # R standard plot is used instead of ggplot

## End(Not run)
```

Description

Provides the possibility of using functions in the package through an interactive graphical user interface (GUI). Depending on input, different GUIs are opened.

Usage

```
## S4 method for signature 'sdmModels'  
gui(x,...)
```

Arguments

x	a sdm* object
...	not implemented yet.

Details

When x is missing, a GUI is opened to facilitate all the steps required to create sdmData, specify the settings for the different steps, and fit sdm models. Specifying x would be useful to interact with sdm* object. For example, if x is a sdmModels (that is generated by sdm function), a user can interactively explore the results (e.g., to see different plots of model evaluation results).

Value

A HTML page in browser is opened.

Author(s)

Babak Naimi <naimi.b@gmail.com>
<http://r-gis.net>
<http://biogeoinformatics.org>

Examples

```
## Not run:  
file <- system.file("external/model.sdm", package="sdm")  
  
m <- read.sdm(file) # a sdmModels Object (fitted using sdm function)  
  
m  
  
gui(m)  
  
## End(Not run)
```

installAll	<i>install all packages that may be required by the package</i>
------------	---

Description

This function facilitates to install the required packages that some functions are dependent on in the sdm package. It first checks whether the package is already installed, and if not, it installs the packages. If update=TRUE is used, the packages re-installed if they were already installed.

Usage

```
installAll(pkgs, update, ...)
```

Arguments

pkgs	optional. the user provided list of packages (not required for the purpose of this function)
update	logical (default=FALSE), specifies whether the packages re-installed if they are already installed on the machine
...	Additional arguments passed to the install.packages function

Author(s)

Babak Naimi <naimi.b@gmail.com>
<http://r-gis.net>
<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, DOI: 10.1111/ecog.01881

See Also

#

Examples

```
## Not run:  
  
installAll()  
  
## End(Not run)
```

names	<i>Names of species</i>
-------	-------------------------

Description

Get or set the names of the species of a sdmdata object

Usage

```
## S4 method for signature 'sdmdata'
names(x)

## S4 replacement method for signature 'sdmdata'
names(x)<-value
```

Arguments

x	A sdm data object (sdmdata)
value	character (vector)

Value

For names, a character
For names<-, the updated object.

Author(s)

Babak Naimi <naimi.b@gmail.com>
<http://r-gis.net>
<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, 39:368-375, DOI: 10.1111/ecog.01881

Examples

```
file <- system.file("external/data.sdd", package="sdm")
d <- read.sdm(file)
d
names(d) # returns the names of species
```

niche *Generate and plot Ecological Niche*

Description

This function maps the species data (either presence/absence or probability of occurrence/habitat suitability) into a two-dimensional environmental space (i.e., based on two environmental variables) to characterise ecological niche based on the specified environmental variables.

Usage

```
niche(x,h,n,.size,plot,out,...)
```

Arguments

x	A Raster* object (or sdmdata) containing environmental variables
h	A RasterLayer, or SpatialPoints, or sdmdata object that represents species data either in the form of habitat suitability (e.g., probability of occurrence) or presence-absence (or even presence-only) data
n	A character vector specifying the names of environmental variables (two names) that should be used to map the ecological niche; if h is a SpatialPoints or sdmdata object, a third name may be added specifying the species name (e.g., the name of the column in SpatialPointsDataFrame contains species data)
.size	optional; a numeric value (default: 1e6) specifies the size of the maximum number of records should be used to generate the ecological niche map; would be useful when the Raster* object introduced in x is big, then a random sample with the specified .size will be drawn based on which the niche is generated
plot	logical, specifies whether the generated niche should be plotted
out	logical, specifies whether the niche should be returned by the function; it will be TRUE if plot is FALSE
...	additional arguments including the argument gg (see details) and other arguments that passed to the plot function

Details

As an additional argument, a user may specify gg which is logical, specifies whether the plot should be generated using the ggplot2 package (if the package is installed), otherwise, the raster package is used to generate the plot.

- . . . : additional arguments for the plot function (e.g., xlab, ylab, main, col, ...) can be used with the function

Value

an object of class .nicheRaster that contains some information about the environmental variable, and a RasterLayer (100x100) that represents the two-dimensional ecological niche.

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, 39:368-375, DOI: 10.1111/ecog.01881

Examples

```
## Not run:

file <- system.file("external/species.shp", package="sdm") # get the location of the species data

species <- shapefile(file) # read the shapefile

path <- system.file("external", package="sdm") # path to the folder contains the data

lst <- list.files(path=path,pattern='asc$',full.names = T) # list the name of the raster files

# stack is a function in the raster package, to read/create a multi-layers raster dataset
preds <- stack(lst) # making a raster object

names(preds) # 4 environmental variables are used!

d <- sdmData(formula=Occurrence~., train=species, predictors=preds)

d

# fit models:
m <- sdm(Occurrence~.,data=d,methods=c('rf','glm','brt'))

# ensemble using weighted averaging based on AUC statistic:
p1 <- ensemble(m, newdata=preds,filename='ens1.grd',setting=list(method='weighted',stat='AUC'))
plot(p1, main='Habitat Suitability in Geographic Space')

# Mapping Ecological Niche using selected two variables
niche(x=preds, h=p1, c('precipitation','temperature'))

niche(x=preds, h=p1, c('vegetation','temperature'))

# in case if you do not have the habitat suitability map but species data:

niche(x=preds, h=species, c('vegetation','temperature','Occurrence'))

niche(x=preds, h=d, n=c('vegetation','temperature','Occurrence'))
```



```
## End(Not run)
```

predict	<i>sdm model prediction</i>
---------	-----------------------------

Description

Make a Raster or matrix object (depending on input dataset) with predictions from one or several fitted models in `sdmModels` object.

Usage

```
## S4 method for signature 'sdmModels'
predict(object, newdata, filename="", w=NULL, species=NULL
        ,method=NULL,replication=NULL,run=NULL,mean=FALSE,control=NULL,
        overwrite=TRUE,nc=1,obj.size=1, ...)
```

Arguments

<code>object</code>	<code>sdmModels</code> object
<code>newdata</code>	Raster* object, or <code>data.frame</code>
<code>filename</code>	character, output file name, if missing, a name starts with <code>sdm_prediction</code> will be generated
<code>w</code>	numeric, specifies which model(s) should be used if the object contains several models; with <code>NULL</code> all models are used
<code>species</code>	character, (optional), specifies which species should be used if the object contains models for multiple species; with <code>NULL</code> all species are used
<code>method</code>	character, names of fitted models, e.g., <code>glm</code> , <code>brt</code> , etc.
<code>replication</code>	character, specifies the names of replication method, if <code>NULL</code> , all available replications are considered
<code>run</code>	numeric, works if replication with multiple runs are used
<code>mean</code>	logical, works if replication with multiple runs are used to fit the models, and specifies whether a mean should be calculated over all predictions of a replication method (e.g., bootstrapping) for each modelling method.
<code>control</code>	not implemented yet!
<code>overwrite</code>	logical, whether the filename should be overwritten if it does exist
<code>nc</code>	number of cores for parallel running of the function
<code>obj.size</code>	the size of object can be kept in memory (default=1 Giga byte). Depending on the available memory, this value can be changed
<code>...</code>	additional arguments, as for <code>writeRaster</code>

Details

predict uses the fitted models in the sdmModel to generate the prediction given newdata. A raster (if newdata is Raster object) or data.frame (if newdata is data.frame) will be created.

The predictions can be generated for a specific set of models in the input sdmModels by determining either or a combination of the name of

For each prediction, a name is assigned which is kind of abbreviation or coding that tells which species, which method, which replication method, and which run is the prediction for. If the output is a Raster object, [setZ](#) function can be used to get a full name of each layer.

Value

a Raster object or data.frame

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, 39:368-375, DOI: 10.1111/ecog.01881

See Also

#

Examples

```
## Not run:

file <- system.file("external/species.shp", package="sdm") # get the location of the species data
species <- shapefile(file) # read the shapefile

path <- system.file("external", package="sdm") # path to the folder contains the data

lst <- list.files(path=path,pattern='asc$',full.names = T) # list the name of the raster files

# stack is a function in the raster package, to read/create a multi-layers raster dataset
preds <- stack(lst) # making a raster object

d <- sdmData(formula=0ccurrence~., train=species, predictors=preds)

d

# fit the models (5 methods, and 10 replications using bootstrapping procedure):
```

```

m <- sdm(Occurrence~,data=d,methods=c('rf','tree','fda','mars','svm'),
        replicatin='boot',n=10)

# predict for all the methods and replications:
p1 <- predict(m, newdata=preds, filename='preds.img')
plot(p1)

# predict for all the methods but take the mean over all replications for each replication method:
p2 <- predict(m, newdata=preds, filename='preds.img',mean=T)
plot(p2)

## End(Not run)

```

rcurve

Generate and plot response curves

Description

Calculate the response of species to the range of values in each predictor variable based on the fitted models in a sdmModels object.

Usage

```
rcurve(x,n,id,mean,confidence,gg,...)
```

```
getResponseCurve(x,id,...)
```

Arguments

x	A sdmModels object; in the function response, it can be a .responseCurve object which is the output of the getResponse function
id	specifies the modelIDs corresponding to the models in the sdmModels object for which the response curves should be generated
n	A vector with the name of variables for which the response curve should be generated
mean	logical, specifies whether a mean should be calculated over responses to a variable when multiple models are specified in ids
confidence	logical, specifies whether a confidence interval should be added to the curve when the mean response curve is calculated based on multiple models
gg	logical, specifies whether the plot should be generated using the ggplot2 package (if the package is installed)
...	additional arguments passed to plot function

Details

`getResponseCurve` calculates the responses for the models that are specified in `id` argument, and put the results in a `.responseCurve` object. This object can be used as an input in the `plot` function, or `rcurve` function.

If you just need the response curve graphs (plots), you can put a `sdmModels` object directly in the `rcurve` function, and do not need to first use `getResponseCurve` function.

In `getResponseCurve` function (or in `rcurve` when `x` is `sdmModels`), there are some additional arguments:

- `size`: a numeric value; default is 100. Specifies the size of the variable sequence that is used as the x-axis in the response curve plot. Greater number results to a smoother curve.
- `includeTest`: a logical value; default is FALSE; when a data object based on which a `sdmModels` is created containing independent test data; it specifies whether those records should be included into the response curve generation or not.
- `...`: additional arguments for the plot function (e.g., `xlab`, `ylab`, `main`, `col`, `lwd`, `lty`)

Value

an object of class `.responseCurve` or a series of graphs

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, 39:368-375, DOI: 10.1111/ecog.01881

Examples

```
## Not run:
file <- system.file("external/model.sdm", package="sdm")

m <- read.sdm(file) # a sdmModels Object (fitted using sdm function)

rcurve(m)

rcurve(m,id=1) # for the first model

rcurve(m, id=1:2)

rcurve(m,method = 'glm',smooth = T) # only for models fitted using glm method & with smoothed curve
```

```
## End(Not run)
```

read.sdm	<i>read/write sdm* object from/to a file</i>
----------	--

Description

Read an sdm object from a file, or write it to a file.

Usage

```
read.sdm(filename, ...)
```

```
write.sdm(x, filename, overwrite, ...)
```

Arguments

filename	Filename (character)
x	a sdm object (e.g., sdmModels, sdmdata or sdmSetting)
overwrite	Logical. If TRUE, "filename" will be overwritten if it exists (default is FALSE)
...	additional arguments

Details

read.sdm function reads any files that has been written by write.sdm. These functions use [saveRDS](#) and [readRDS](#) to write and read the sdm objects. Additional arguments ... pass to these functions. An sdmModels object is saved to a file with an extension of ".sdm". The file extensions for sdmdata and sdmSetting object are ".sdd", and "sds", respectively.

Author(s)

Babak Naimi
<naimi@r-gis.net>
<http://r-gis.net>
<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, 39:368-375, DOI: 10.1111/ecog.01881

Examples

```
## Not run:

file <- system.file("external/data.sdd", package="sdm")

d <- read.sdm(file)

d
# can be used to read sdm models (sdmModels) and sdmSettings as well.

write.sdm(d,'dataset')
# extension is created for data, model and settings as .sdd, .sds, and .sdm respectively.

list.files(pattern='dataset')

## End(Not run)
```

roc

plot ROC curves

Description

Plot the Receiver Operating Characteristics (ROC) curve with AUC statistic in the legend.

Usage

```
roc(x,p=NULL,species=NULL,method=NULL,replication=NULL,run=NULL,
    wtest=NULL,smooth=FALSE,legend=TRUE,...)
```

```
getRoc(x,p,...)
```

Arguments

x	Either sdmModels, or sdmEvaluate object; or a numeric vector including observed binary values of species occurrence
p	if x is sdmModels, p is an optional vector with model ID number(s) that should be plotted (NULL (default means all models)); if x is a numeric vector, p is a vector with the same length including the predicted values
species	the name of species should be specified (required if x is sdmModels containing models for several species)
method	a character vector with the name of modelling methods that one need to get the roc plot for (if NULL [default], all methods in the object are considered); only if x is sdmModels
replication	a character vector with the name of replication methods (i.e., 'sub','cv','boot') that one need to get the roc plot for

run	if x is sdmModels, and the models are fitted through a replication procedure, run specifies which runs of the partitioning (replications) are required; if NULL, all are considered
wtest	evaluation for which test datasets are required, maximum 2 names from 'training', 'test.dep', 'test.indep' (i.e., evaluation for training data, dependent test dataset, and independent test dataset, respectively)
smooth	logical, specified whether the ROC curves should be smoothed through a spline procedure
legend	logical, specified whether a legend including AUC statistic is required on the plot
...	additional arguments passed to plot function

Details

roc generates the plots of roc curves, and getRoc generate the values of ROC

Value

an object of class matrix

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, 39:368-375, DOI: 10.1111/ecog.01881

Examples

```
## Not run:
file <- system.file("external/model.sdm", package="sdm")

m <- read.sdm(file) # a sdmModels Object (fitted using sdm function)

roc(m)

roc(m,1) # for the first model

roc(m, 1:2)

roc(m,method = 'glm',smooth = T) # only for models fitted using glm method & with smoothed curve

## End(Not run)
```

`sdm`*Fit and evaluate species distribution models*

Description

Fits `sdm` for single or multiple species using single or multiple methods specified by a user in `methods` argument, and evaluates their performance.

Usage

```
sdm(formula, data, methods, ...)
```

Arguments

<code>formula</code>	Specifies the structure of the model, types of features, etc.
<code>data</code>	a <code>sdmdata</code> object created using <code>sdmData</code> function
<code>methods</code>	Character. Specifies the methods, used to fit the models
<code>...</code>	additional arguments

Details

`sdm` fits multiple models and can be used to generate multiple runs (replicates) of each method through partitioning (using one or several partitioning methods including: subsampling, cross-validation, and bootstrapping).

Each model is evaluated against training data, and if available, splitted data (through partitioning; called dependent test data as well, i.e., "dep.test") and/or independent test data ("indep.test").

User should make sure that the methods are available and the required packages for them are installed before putting their names in the function, otherwise, the methods that cannot be run for any reason, are excluded by the function. It is a good practice to call `installAll` function (just one time when the `sdm` is installed), that tries to install all the packages that may be needed somewhere in the `sdm` package.

A new method can be adopted and added to the package by a user using `add` function. It is also possible to get an instance of an existing method, override the setting and definition, and then add it with a new name (e.g., `my.glm`).

The output would be a single object (`sdmModels`) that can be read/reproduced everywhere (e.g., on a new machine). A setting object can also be taken (exported) out of the output `sdmModels` object, that can be used to reproduce the same practice but given new conditions (i.e., new dataset, area, etc.)

Value

an object of class `sdmModels`

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, 39:368-375, DOI: 10.1111/ecog.01881

Examples

```
## Not run:
file <- system.file("external/pa_df.csv", package="sdm")

df <- read.csv(file)

head(df)

d <- sdmData(sp~b15+NDVI,train=df)

d
#----
# Example 1: fit using 3 models, and no evaluation (evaluation based on training dataset):

m <- sdm(sp~b15+NDVI,data=d,methods=c('glm','gam','gbm'))

m

# Example 3: fit using 5 models, and
# evaluates using 10 runs of subsampling replications taking 30 percent as test:

m <- sdm(sp~b15+NDVI,data=d,methods=c('glm','gam','gbm','svm','rf'),
        replication='sub',test.percent=30,n=10)

m

# Example 3: fits using 5 models, and
# evaluates using 10 runs of both 5-folds cross-validation and bootstrapping replication methods

m <- sdm(sp~.,data=d,methods=c('gbm','tree','mars','mda','fda'),
        replication=c('cv','boot'),cv.folds=5,n=10)

m

# Example 4: fit using 3 models; evaluate the models using subsampling,
# and override the default settings for the method brt:

m <- sdm(sp~b15+NDVI,data=d,methods=c('glm','gam','brt'),test.p=30,
        modelSettings=list(brt=list(n.trees=500,train.fraction=0.8)))
```

```

m

## End(Not run)

```

```

sdmCorrelativeMethod-class
      sdmCorrelativeMethod class

```

Description

An S4 class representing sdm dataset

Slots

name Modelling method name
aliases Alternative names for the method
dataArgument.names A list keeps the name of data arguments in both fit and predict functions
packages The required external package by the method
modelTypes Specifies whether the model is presence-absence, presence-only, abundance, or multinomial
fitParams a list of parameters needed by the method
fitSettings a list of setting parameters for the method
settingRules a function that adjust the setting parameters according to data
fitFunction The main function use for fitting the model
tuneParams a list of parameters to be tuned before the final fitting
predictParams a list of parameters needed by predict function
predictSettings a list of setting parameters for prediction
predictFunction The main predict function
metadata a metadata object containing the information about who creates the object, date, etc.
.temp.env an environment object containing the functions defined by a user that is not from a package

sdmData *creating sdm Data object*

Description

Creates a sdmData objects that holds species (single or multiple) and explanatory variates. In addition, more information such as spatial coordinates, time, grouping variables, and metadata (e.g., author, date, reference, etc.) can be included.

Usage

```
sdmData(formula, train, test, predictors, bg, filename, crs, ...)
```

Arguments

formula	Specifies which species and explanatory variables should be taken from the input data. Other information (e.g., spatial coordinates, grouping variables, time, etc.) can be determined as well
train	Training data containing species observations as a data.frame or SpatialPoints or SpatialPointsDataFrames. It may contain predictor variables as well
test	Independent test data with the same structure as the train data
predictors	explanatory variables (predictors), defined as a raster object (RasterStack or RasterBrick). Required if train data only contain species records, or background records (pseudo-absences) should be generated
bg	Background data (pseudo-absence), as a data.frame. It can also be a list contains the settings to generate background data (a Raster object is required in the predictors argument)
filename	filename of the sdm data object to store in the disk
crs	optional, coordinate reference system
...	Additional arguments (optional) that are used to create a metadata object. See details

Details

sdmData creates a data object, for single or multiple species. It can automatically detect the variables containing species data (if a data.frame is provided in train), but it is recommended to use formula through which all species (in the left hand side, e.g., sp1+sp2+sp3 ~ .), and the explanatory variables (in the right hand side) can be determined. If there are additional information such as spatial coordinates, time, or some variables based on which the observation can be grouped, they can be determined in the right hand side of the formula in a flexible way (e.g., ~ . + coords(x+y) + g(var); This right hand side formula, simply determines all variables (.) + x and y as spatial coordinates + grouping observations based on the variable var; for grouping, the variable (var in this example) should be categorical, i.e., factor).

Additional arguments can be provided to determine metadata information including: author, website, citation, help, description, date, and license

Value

an object of class `sdmdata`

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, 39:368-375, DOI: 10.1111/ecog.01881

Examples

```
## Not run:
# Example 1: a data.frame containing records for a species (sp) and two predictors (b15 & NDVI):

file <- system.file("external/pa_df.csv", package="sdm")

df <- read.csv(file)

head(df)

d <- sdmData(sp~b15+NDVI,train=df)

d

# or simply:
d <- sdmData(sp~.,train=df)

d

#-----
# if formula is not specified, function tries to detect species and covariates, it works well only
# if dataset contains no additional columns but species and covariates!

d <- sdmData(train=df)

d

# # only right hand side of the formula is specified (one covariate), so function detects species:
d <- sdmData(~NDVI,train=df)

d

#-----
#####
# Example 2: a data.frame containing presence-absence records for 1 species, 4 covariates, and
# x, y coordinates:
```

```

file <- system.file("external/pa_df_with_xy.csv", package="sdm")

df <- read.csv(file)

head(df)

d <- sdmData(sp~b15+NDVI+categoric1+categoric2+coords(x+y),train=df)

d
#----
# categoric1 and categoric2 are categorical variables (factors), if not sure the data.frame has
# them as factor, it can be specified in the formula:
d <- sdmData(sp~b15+NDVI+f(categoric1)+f(categoric2)+coords(x+y),train=df)

d
# more simple forms of the formula:
d <- sdmData(sp~.+coords(x+y),train=df)

d

d <- sdmData(~.+coords(x+y),train=df) # function detects the species

d
#####
# Example 3: a data.frame containing presence-absence records for 10 species:

file <- system.file("external/multi_pa_df.csv", package="sdm")

df <- read.csv(file)

head(df)

# in the following formula, spatial coordinates columns are specified, and the rest is asked to
# be detected by the function:
d <- sdmData(~.+coords(x+y),train=df)

d

#--- or it can be customized with species and which covariates are needed:
d <- sdmData(sp1+sp2+sp3~b15+NDVI+f(categoric1) + coords(x+y),train=df)

d # 3 species, 3 covariates, and coordinates
# just be careful that if you put "." in the right hand side, while not all species columns or
# additional columns (e.g., coordinates, time) are specified in the formula, then it takes those
# columns as covariates which is NOT right!

#####
# Example 4: Spatial data:

file <- system.file("external/pa_spatial_points.shp", package="sdm") # path to a shapefile

# use a package like rgdal, or maptools, or shapefile function in package raster to read shapefile:

```

```

p <- shapefile(file)
class(p) # a "SpatialPointsDataFrame"

plot(p)

head(p) # it contains data for 3 species

# presence-absence plot for the first species (i.e., sp1)
plot(p[p@data$sp1 == 1,],col='blue',pch=16, main='Presence-Absence for sp1')

points(p[p@data$sp1 == 0,],col='red',pch=16)

# Let's read raster dataset containing predictor variables for this study area:

file <- system.file("external/predictors.grd", package="sdm") # path to a raster object

r <- brick(file)

r # a RasterBrick object including 2 rasters (covariates)

plot(r)

# now, we can use the species points and predictor rasters in sdmData function:
d <- sdmData(sp1+sp2+sp3~b15+NDVI,train=p,predictors = r)

d

#####
# Example 5: presence-only records:

file <- system.file("external/po_spatial_points.shp", package="sdm") # path to a shapefile

# use an appropriate function to read the shapefile (e.g., readOGR in rgdal, readShapeSpatial in
# maptools, or shapefile in raster):

po <- shapefile(file)
class(po) # a "SpatialPointsDataFrame"

head(po) # it contains data for one species (sp4) and the column has only presence records!

d <- sdmData(sp4~b15+NDVI,train=po,predictors = r)

d # as you see in the type, the data is Presence-Only

### we can add another argument (i.e., bg) to generate background (pseudo-absence) records:

#----- in bg, we are going to provide a list containing the setting to generate background
#----- the setting includes n (number of background records), method (the method used for
#----- background generation; gRandom refers to random in geographic space), and remove (whether

```

```

#----- points located in presence sites should be removed).
d <- sdmData(sp4~b15+NDVI,train=po,predictors = r,bg=list(n=1000,method='gRandom',remove=TRUE))
d      # as you see in the type, the data is Presence-Background
# you can alternatively, put a data.frame including background records in bg!
## End(Not run)

```

sdmdata-class *An S4 class representing sdm dataset*

Description

An S4 class representing sdm dataset sdmdata

Slots

species.names The names of species
species Contains the species data
features.name The names of predictor variables
features A data.frame containing predictor variables
factors The names of categorical variables (if any)
info Other information such as coordinates, metadata, etc.
groups A list including information on groups in the dataset
sdmFormula An object of class sdmFormula containing the formula and its' terms defined by user
errorLog Reports on errors in the data raised through data cleaning (e.g., NA, duplications, etc.)

Author(s)

Babak Naimi <naimi.b@gmail.com>
<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, DOI: 10.1111/ecog.01881

sdmModels-classes *sdmModels classes*

Description

An S4 class to keep all the information of fitted models as well as their evaluations.

Slots

Slots for sdmModels objects:

data a sdmdata object

recordIDs Contains the species data

setting A data.frame containing predictor variables

run.info a data.frame containing info on runs

replicates The names of categorical variables (if any)

models a list contains all fitted objects and relevant information (e.g., evaluation)

Slots for sdmEvaluate objects:

observed a numeric vector of observed values

predicted a numeric vector of predicted values

statistics a list of threshold-independent statistics

threshold_based a data.frame of threshold-based statistics

Slots for sdmFormula objects:

formula input formula

vars character, name of variables

model.terms the formula terms used in model fitting

data.terms the formula terms used to manipulate data

Author(s)

Babak Naimi

<naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

sdmSetting	<i>creating sdmSetting object</i>
------------	-----------------------------------

Description

Creates `sdmSetting` object that holds settings to fit and evaluate the models. It can be used to reproduce a study.

Usage

```
sdmSetting(formula,data,methods,interaction.depth=1,n=1,replication=NULL,cv.folds=NULL,
  test.percent=NULL,bg=NULL,bg.n=NULL,var.importance=NULL,response.curve=TRUE,
  var.selection=FALSE,ncore=1L,modelSettings=NULL,seed=NULL,parallelSettings=NULL,...)
```

Arguments

<code>formula</code>	specify the structure of the model
<code>data</code>	sdm data object or <code>data.frame</code> including species and feature data
<code>methods</code>	character, name of the algorithms
<code>interaction.depth</code>	level of interactions between predictors
<code>n</code>	number of replicates (run)
<code>replication</code>	replication method (e.g., 'subsampling', 'bootstrapping', 'cv')
<code>cv.folds</code>	number of folds if cv (cross-validation) is in the selected replication methods
<code>test.percent</code>	test percentage if subsampling is in the selected replication methods
<code>bg</code>	method to generate background
<code>bg.n</code>	number of background records
<code>var.importance</code>	logical, whether variable importance should be calculated
<code>response.curve</code>	method to calculate variable importance
<code>var.selection</code>	logical, whether variable selection should be considered
<code>ncore</code>	number of cores to parallelize processing
<code>modelSettings</code>	optional list; settings for modelling methods can be specified by users
<code>seed</code>	default is <code>NULL</code> ; either logical specify whether a seed for random number generator should be considered, or a numerical to specify the exact seed number
<code>parallelSettings</code>	default is <code>NULL</code> ; a list include settings items for parallel processing. The parallel setting items include <code>ncore</code> , <code>method</code> , <code>type</code> , <code>hosts</code> , <code>doParallel</code> , and <code>fork</code> ; see details for more information.
<code>...</code>	additional arguments

Details

using `sdmSetting`, the feature types, `interaction.depth` and all settings of the model can be defined. This function generate a `sdmSetting` object that can be specifically helpful for reproducibility. The object can be shared by a user that may be used for other studies.

If a user aims to reproduce the same results for every time the code is running with the same data and settings, a seed number should be specified. Through the `seed` argument, a user can specify `NULL`, means a seed should not be set (if a random sampling is incorporated in the modelling procedure, for different runs the results would be different); `TRUE`, means a seed should be set (the seed number is randomly selected and used everytime the same setting is incorporated); a number, means the seed will be set to the number specified by the user.

For parallel processing, a list of items can be passed to `parallelSettings`, include:

`ncore`: defines the number of cores (it can also be specified outside of this list, but will be removed in future)

`method`: defines the platform/set of functions to run the parallelisation. Currently, two options of 'parallel', and 'foreach' is implemented. default is 'parallel'

`doParallel`: Optional, definition to register for a backend for parallel processing (currently when `method='foreach'`). It should be provided as an R expression.

`cluster`: Optional, if a cluster is already created and started, it can be introduced through this item to be used as the parallel processing platform (currently when `method='parallel'`)

`hosts`: A list of addresses for the accessible hosts (remote clusters) to be registered and used in parallel processing (may not work appropriately as it is still under development!)

`fork`: Logical, Available for non-windows operating system and specifies whether a fork solution should be used for the parallelisation. Default is `TRUE`.

Value

an object of class `sdmSettings`

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, DOI: 10.1111/ecog.01881

Examples

```
## Not run:
file <- system.file("external/pa_df.csv", package="sdm")

df <- read.csv(file)
```

```

head(df)

d <- sdmData(sp~b15+NDVI,train=df)

# generate sdmSettings object:
s <- sdmSetting(sp~., methods=c('glm','gam','brt','svm','rf'),
  replication='sub',test.percent=30,n=10,modelSettings=list(brt=list(n.trees=500)))

s

## End(Not run)

```

subset	<i>Subset models in a sdmModels object</i>
--------	--

Description

This function extracts a subset of models from a `sdmModels` object. It generates a new object of the same type as the original object. In `sdmModels`, `modelID` provides the unique IDs.

Instead of using the `subset` function, double brackets `'[[]]`' can be used.

Details

#

Value

`sdmModels` object

Methods

```
subset(x, subset, drop=TRUE, ...)
```

```
x[[i, ...]]
```

Arguments:

`x` - `sdmModels` object

`i` - integer. Indicates the index/id of the models (`modelID`) should be extracted from `sdmModels` object

`subset` - Same as `i`

`drop` - If `TRUE`, new `modelIDs` are generated, otherwise, the original `modelIDs` are kept in the new object.

`...` - additional arguments (not implemented yet!)

Author(s)

Babak Naimi <naimi.b@gmail.com>

<http://r-gis.net>

<http://biogeoinformatics.org>

References

Naimi, B., Araujo, M.B. (2016) sdm: a reproducible and extensible R platform for species distribution modelling, *Ecography*, DOI: 10.1111/ecog.01881

Examples

```
## Not run:
file <- system.file("external/model.sdm", package="sdm")

m <- read.sdm(file)

m

getModelInfo(m)

m1 <- m[[3:4]]

m1

getModelInfo(m1)

m2 <- m[[3:4,drop=FALSE]]

m2

getModelInfo(m2)

#---- the following is the same as previous:

m2 <- subset(m,3:4,drop=FALSE)

m2

getModelInfo(m2)

## End(Not run)
```

Index

- *Topic **accuracy**
 - evaluates, 13
 - roc, 30
- *Topic **classes**
 - sdmModels-classes, 40
- *Topic **data**
 - boxplot, 6
 - calibration, 7
 - coordinates, 8
 - density, 9
 - evaluates, 13
 - featuresFrame-class, 16
 - niche, 23
 - predict, 25
 - sdm, 32
 - sdmData, 35
 - sdmdata-class, 39
 - sdmSetting, 41
- *Topic **extensible**
 - add, 2
- *Topic **interface**
 - gui, 19
- *Topic **learning**
 - ensemble, 10
- *Topic **math**
 - Arith-methods, 4
- *Topic **methods**
 - Arith-methods, 4
 - as.data.frame, 5
 - Extract by index, 15
 - featuresFrame-class, 16
 - sdmdata-class, 39
- *Topic **method**
 - add, 2
- *Topic **modelling**
 - ensemble, 10
- *Topic **model**
 - get models' outputs, 16
 - predict, 25
 - roc, 30
 - sdm, 32
 - sdmSetting, 41
- *Topic **sdm**
 - Arith-methods, 4
 - ensemble, 10
 - get models' outputs, 16
 - rcurve, 27
 - read.sdm, 29
- *Topic **spatial**
 - as.data.frame, 5
 - calibration, 7
 - coordinates, 8
 - density, 9
 - ensemble, 10
 - evaluates, 13
 - Extract by index, 15
 - featuresFrame-class, 16
 - getVarImp, 18
 - gui, 19
 - names, 22
 - niche, 23
 - predict, 25
 - rcurve, 27
 - roc, 30
 - sdm, 32
 - sdmData, 35
 - sdmdata-class, 39
 - sdmModels-classes, 40
 - sdmSetting, 41
 - subset, 43
- *Topic **species**
 - niche, 23
 - sdm, 32
 - sdmData, 35
 - sdmdata-class, 39
- *Topic **utilities**
 - installAll, 21
- *Topic **visualise**

- boxplot, 6
- *Topic **write**
 - read.sdm, 29
- +, sdmModels, sdmModels-method (Arith-methods), 4
- [, sdmdata, ANY, ANY-method (Extract by index), 15
- [, sdmdata, missing, missing-method (Extract by index), 15
- [[, sdmModels, ANY, ANY-method (subset), 43
- add, 2, 32
- add, list, character-method (add), 2
- Arith-methods, 4
- as.data.frame, 5
- as.data.frame, sdmdata-method (as.data.frame), 5
- boxplot, 6, 6
- boxplot, sdmEvaluate-method (boxplot), 6
- calibration, 7
- calibration, sdmEvaluate, missing-method (calibration), 7
- calibration, vector, vector-method (calibration), 7
- characterORmissing-class (sdmModels-classes), 40
- characterORnull-class (sdmModels-classes), 40
- coordinates, 8
- coordinates, sdmdata-method (coordinates), 8
- coordinates, sdmModels-method (coordinates), 8
- coordinates<- (coordinates), 8
- coordinates<-, sdmdata-method (coordinates), 8
- CRSorNULL-class (sdmModels-classes), 40
- data.frameORnull-class (sdmModels-classes), 40
- density, 9
- density, sdmEvaluate-method (density), 9
- ensemble, 10
- ensemble, sdmModels, data.frame-method (ensemble), 10
- ensemble, sdmModels, Raster-method (ensemble), 10
- ensemble, sdmModels-method (ensemble), 10
- environmentORnull-class (sdmModels-classes), 40
- evaluates, 13
- evaluates, vector, vector-method (evaluates), 13
- expressionORnull-class (sdmModels-classes), 40
- Extract by index, 15
- featuresFrame-class, 16
- formulaORnull-class (sdmModels-classes), 40
- functionORcharacter-class (sdmModels-classes), 40
- functionORnull-class (sdmModels-classes), 40
- get models' outputs, 16
- getEvaluation (evaluates), 13
- getEvaluation, sdmModels-method (evaluates), 13
- getmethod (add), 2
- getmethod, character-method (add), 2
- getmethodNames (add), 2
- getmethodNames, ANY-method (add), 2
- getModelId (get models' outputs), 16
- getModelId, sdmModels-method (get models' outputs), 16
- getModelInfo (get models' outputs), 16
- getModelInfo, sdmModels-method (get models' outputs), 16
- getResponseCurve (rcurve), 27
- getResponseCurve, sdmModels-method (rcurve), 27
- getRoc (roc), 30
- getRoc, sdmModels, ANY-method (roc), 30
- getRoc, vector, vector-method (roc), 30
- getVarImp, 18
- getVarImp, sdmModels-method (getVarImp), 18
- gui, 19
- gui, sdmModels-method (gui), 19
- install.packages, 21
- installAll, 21, 32
- installAll, ANY-method (installAll), 21
- listORcharacter-class (sdmModels-classes), 40

- listORnull-class (sdmModels-classes), 40
- matrixORnull-class (sdmModels-classes), 40
- names, 22
- names, sdmdata-method (names), 22
- names<- (names), 22
- names<- , sdmdata-method (names), 22
- niche, 23
- niche, RasterStackBrick, RasterLayer-method (niche), 23
- niche, RasterStackBrick, sdmdata-method (niche), 23
- niche, RasterStackBrick, SpatialPoints-method (niche), 23
- niche, sdmdata, ANY-method (niche), 23
- numericORnull-class (sdmModels-classes), 40
- plot, .nicheRaster-method (niche), 23
- plot, .responseCurve-method (rcurve), 27
- predict, 25
- predict, .maxlikeModel-method (predict), 25
- predict, sdmModels-method (predict), 25
- rcurve, 27
- rcurve, .responseCurve-method (rcurve), 27
- rcurve, sdmModels-method (rcurve), 27
- read.sdm, 29
- read.sdm, character-method (read.sdm), 29
- readRDS, 29
- roc, 30
- roc, sdmModels, ANY-method (roc), 30
- roc, sdmModels-method (roc), 30
- roc, vector, vector-method (roc), 30
- saveRDS, 29
- sdm, 16, 32
- sdm, ANY, sdmdata, .sdmCorSetting-method (sdm), 32
- sdm, ANY, sdmdata, character-method (sdm), 32
- sdm, sdmdata, .sdmCorSetting, ANY-method (sdm), 32
- sdmCorrelativeMethod-class, 34
- sdmData, 32, 35
- sdmData, ANY, data.frame, ANY, missing-method (sdmData), 35
- sdmData, ANY, data.frame, missing, missing-method (sdmData), 35
- sdmData, ANY, SpatialPoints, ANY, missing-method (sdmData), 35
- sdmData, ANY, SpatialPoints, ANY, Raster-method (sdmData), 35
- sdmData, data.frame, formula, ANY, missing-method (sdmData), 35
- sdmData, data.frame, missing, ANY, missing-method (sdmData), 35
- sdmdata-class, 39
- sdmEvaluate-class (sdmModels-classes), 40
- sdmFormula-class (sdmModels-classes), 40
- sdmModels-class (sdmModels-classes), 40
- sdmModels-classes, 40
- sdmSetting, 41
- sdmSetting, ANY, sdmdata, character-method (sdmSetting), 41
- setZ, 26
- show, sdmdata-method (sdmdata-class), 39
- show, sdmModels-method (sdmModels-classes), 40
- show, sdmSetting-method (sdmSetting), 41
- subset, 43
- subset, sdmModels-method (subset), 43
- write.sdm (read.sdm), 29
- write.sdm, .sdmCorSetting, character-method (read.sdm), 29
- write.sdm, sdmdata, character-method (read.sdm), 29
- write.sdm, sdmModels, character-method (read.sdm), 29
- writeRaster, 25